

Floor To Floor Models

F2F-050

EZLIFT®

The E-Z LIFT Floor to Floor conveyor is specially designed to move passenger car and light truck tires up to 60 degree inclines.

Features Include:

- 18" wide 2 ply rubber covered top belt sliding flat at 58 FPM
- 4" high urethane cleats bolted to the belt on approximately 60" centers
- Curved cleat pattern to fit tire contour
- One Up/Stop/Down switch at the bottom end
- 1hp 115V 13 FLA electric motor with speed reducer mounted under bottom end
- Thermal overload motor protector
- All electrical prewired
- Rubber lagged conveyor belt drive pulley
- Plain idler pulley with belt tensioner
- Sealed precision bearings
- High strength steel tubing truss conveyor frame
- Base Plate

Accessories:

- Off switch at the top end
- Portable stand with casters to hold top end at fixed height
- Portable stand with casters with hand winch adjustable top end height

Options:

- Up/Emergency Stop/Down switches at both ends of conveyor with UL Listing
- Straight cleats for handling boxes, bags, and general merchandise
- Smooth or rough top belt for shallow inclines

10 ft. long and up in 1 ft. increments

Model	Length	Approx. Wgt.*
F2F12	12 ft.	295 lbs.
F2F15	15 ft.	330 lbs.
F2F18	18 ft.	365 lbs.
F2F21	21 ft.	400 lbs.



Multilift, Inc.

2000 South Cherokee, Denver, Colorado 80223
 Denver Area: 303.733.5533 FAX 303.733.5642
 North American Toll Free: 1.800.821.9966



Portable stand w/hand winch adjustment



Specifications subject to change without notice
 *Weight w/o accessories