





The E-ZLIFT Floor to Floor conveyor is specially designed to move passenger car and light truck tires up to 60 degree inclines or 90 degrees vertical.

UL Listed Standard Features:

- 18" wide, 2 ply rubber covered top belt, sliding flat at 58 FPM
- 4" high, urethane cleats (2 per set) bolted to the belt on approximately 60" centers
- · Curved cleat pattern to fit tire contour
- One Forward/Emergency Stop/Reverse push button main station mounted at the bottom end of the conveyor and one Forward/Emergency Stop/Reverse push button station mounted at the top end
- 1hp 115V 13 FLA electric motor with speed reducer mounted under bottom end
- · Thermal overload motor protector
- · All electrical prewired
- · Rubber lagged conveyor belt drive pulley
- · Plain idler pulley with belt tensioner

UL Listed Installation

- · High strength steel tubing truss conveyor frame
- · Base Plate for bolting conveyor to the floor
- · Coil Chain with connecting link for securing top end of conveyor to the
- Conveyor lengths from 10 ft. to 23 ft. available, in 1 ft. increments

Options:

UL Listed

- 24 ft. thru 31 ft. lengths, motor and speed reducer mounted at the top end
- 18" and 24" wide belts, all lengths thru 31 ft.
- 6" high cleats (2 per set), bolted to belt on approximately 60" centers, curved cleat pattern to fit tire contour

Non-UL Listed

- · Vertical design with 6" high single cleats for 90 degree tire conveying
- One Up/Stop/Down switch mounted at the bottom of the conveyor
- · Off switch at the top end
- · Straight cleats for handling boxes, bags, and general merchandise
- · Smooth or rough top belt for shallow inclines

Accessories:

Non-UL Listed

- · Portable stand with casters for fixed height installation
- · Portable stand with casters and hand winch for adjustable height installation



Multilift, Inc.

12410 W Cedar Dr, Lakewood, Colorado 80228 Denver Area: 303.733.5533 Fax: 303.733.5642 North American Toll Free: 1.800.821.9966

E-mail: ez@ezliftconveyors.com Website: www.ezliftconveyors.com

Vertical Installations (Non-UL Listed)

